



**ADVANCED  
TECHNOLOGY  
PRODUCTS**

**Manufacturers of  
Thermoplastic Tubing and Spiral Recoil Hoses**



## TST 2 Stage Coupling

TST's 2 stage push button couplings provides a durable and safe pneumatic quick-disconnect-coupling. TST's 2 stage couplings are a great addition to any pneumatically-powered tool in industrial, automotive, and construction settings. The couplings connect simply by inserting a plug.

Disconnection is accomplished through a two-step push button operation:  
 Step 1: Push button to release downstream pressure  
 Step 2: Push button again to remove plug



### A 14 BC - N2M

Material		Body Size/Interchange		Style		Threads	
A	Aluminum Body	14	1/4" Industrial	BC	Button Coupling	N	NPT
		3/8	3/8" Industrial			2	1/4" Thread
		14A	1/4 ARO			3	3/8" Thread
		25	European			4	1/2" Thread
						M	Male Thread
						F	Female Thread

Specifications	
Operation	2 Stage Push-Button Shutoff
Pressure Range	0 to 174 psi
Temperature Range	-4°F to 212°F
Construction	Nickel Plated Brass & Aluminum

### Fractional Sizes

ATP PN	TST Series	Interchange	Thread
A14BC-N2M	023S.06	1/4" Industrial	1/4" Male NPT
A14BC-N2F			1/4" Female NPT
A14BC-N3M			3/8" Male NPT
A14BC-N3F			3/8" Female NPT
A14BC-N4M			1/2" Male NPT
A14BC-N4F			1/2" Female NPT
A38BC-N2M	030S.08	3/8" Industrial	1/4" Male NPT
A38BC-N2F			1/4" Female NPT
A38BC-N3M			3/8" Male NPT
A38BC-N3F			3/8" Female NPT
A38BC-N4M			1/2" Male NPT
A38BC-N4F			1/2" Female NPT
A14ABC-N2M	022S.06	1/4" ARO	1/4" Male NPT
A14ABC-N2F			1/4" Female NPT
A25BC-N2M	025S.08	European/ High Flow	1/4" Male NPT
A25BC-N2F			1/4" Female NPT